



Integration Guide | PUBLIC

Document Version: 1.1 – 2024-05-15

Integrating Plant Data from SAP S/4HANA Cloud to SAP Integrated Business Planning

Integrating SAP IBP for Supply Chain 2402 with SAP S/4HANA Cloud Using SAP Cloud Integration

Content

- 1 Introduction. 4**
- 2 Prerequisites. 5**
- 3 Configuring the Integration Flow. 6**
 - 3.1 Configuring the Authentication. 6
 - 3.2 Data Mapping. 7
 - 3.3 Defining Additional Parameters. 7
 - 3.4 Working with Field Extensions. 8
 - 3.5 Scheduling the Integration Flow. 11
- 4 Troubleshooting. 12**

Document History

The following table provides an overview of the most important changes.

Version	Date	Description
1.1	May 15, 2024	Minor language and parameter enhancements in Defining Additional Parameters [page 7] section.
1.0	February 16, 2024	Initial version

1 Introduction

Using the integration flow, you can integrate data from SAP S/4HANA Cloud, as part of the solution SAP S/4HANA Cloud Public Edition to SAP Integrated Business Planning for Supply Chain (SAP IBP). Using this data, you can perform demand forecasting in SAP IBP, then integrate the results back to SAP S/4HANA Cloud as planned independent requirements.

Data integration between SAP IBP and SAP S/4HANA Cloud using the integration flows in the *SAP IBP - Integration with SAP S/4HANA Cloud* package is available with SAP IBP 2402 and higher.

Using the *Integrate Plants from SAP S/4HANA Cloud to SAP IBP* integration flow, you can integrate plant data from SAP S/4HANA Cloud to SAP IBP. Plant data is collected using an OData API. For more information about the API, see the API reference at the SAP Business Accelerator Hub at https://api.sap.com/cdsviews/_PLANT.

2 Prerequisites

We recommend that you have configured frequently used parameters using the *Define Default Values for Data Integration Between SAP IBP and SAP S/4HANA Cloud* integration flow.

3 Configuring the Integration Flow

3.1 Configuring the Authentication

The integration flow connects to both the SAP S/4HANA Cloud and the SAP IBP system. Connections, including the authentication method, must be created and configured at different places depending on the respective system. Once the connections are created for both directions, you need to configure them in the integration flow under ► [Configure](#) ► [Receiver](#) ►.

Authentication Methods for the Connection to SAP IBP

You can only choose basic authentication when connecting to SAP IBP. You can configure the authentication method during the configuration of the destination. You can set the name of the destination using the `Destination for SAP IBP` parameter of the integration flow.

For more information, see [Setting Up the Integration](#).

Authentication Methods for the Connection to SAP S/4HANA Cloud

The following authentication methods are available when connecting to SAP S/4HANA Cloud:

- Basic authentication
- Client certificate (X.509 certificate)

You can select the authentication method in the integration flow under ► [Configure](#) ► [Receiver](#) ► [Authentication](#) ►. Although there are more options displayed in the list, only basic authentication and client certificate authentication are supported.

The default authentication method is client certificate.

Setting Up the Client Certificate Authentication Method

As a prerequisite of using a client certificate, add and deploy the required key pair to the keystore. You can do so in SAP Integration Suite using the [Keystore](#) tile in the [Manage Security](#) section under [Monitoring Artifacts](#). For more information, see <https://help.sap.com/docs/cloud-integration/sap-cloud-integration/managing-keystore-entries>.

If you select authentication using a client certificate when configuring the integration flow, you need to enter the private key alias.

Setting Up the Basic Authentication Method

As a prerequisite of using basic authentication, create and deploy the user credentials type of security material. You can do so in SAP Integration Suite using the [Security Material](#) tile in the [Manage Security](#) section under [Monitoring Artifacts](#). For more information, see <https://help.sap.com/docs/cloud-integration/sap-cloud-integration/managing-security-material>.

If you select basic authentication when configuring the integration flow, you need to enter the credential name.

3.2 Data Mapping

The following default data mapping is available in the integration flow:

Property in OData Entity	Field in SAP IBP	Further Hints
Plant	LOCID	
P	LOCTYPE	The property in the OData entity is fixed as P.
PlantName	LOCDESCR	The property is available from the <code>Product</code> entity through the ▶ ProductDescription ▶ ProductDescription_Type ▶ ProductDescription navigation.

3.3 Defining Additional Parameters

Under [▶ Configure](#) [▶ More](#) [▶](#), you can find the following parameters that you can use to configure the integration flow:

Parameter Name	Default Value	How to Configure the Parameter?
Attributes in SAP IBP	LOCID, LOCIDDISPLAY, LOCTYPE, LOCDESCR, LOCREGION	Define the fields of the <code>Location</code> master data in SAP IBP into which you want to integrate data.
Batch Name	Plant: \$ {header.SAP_MplCorrelationId}	Define the name of the data batch. This name also identifies the corresponding job in the Data Integration Jobs app.
Destination for SAP IBP	-keep default-	Enter the name of the target SAP IBP system into which you want to integrate plant data.

Parameter Name	Default Value	How to Configure the Parameter?
Field Extensions		Optionally, you can define complex mappings for certain columns. For more information, see Working with Field Extensions [page 8] .
Host for SAP S/4HANA Cloud	-keep default-	Define the base URL of the SAP S/4HANA Cloud API
Master Data Prefix	-keep default-	Optionally, define a three-character-long prefix to be used in SAP IBP.
Planning Area	-keep default-	Define the planning area in SAP IBP to which you want data to be integrated.
Planning Area Version	-keep default-	Define the version of the target planning area in SAP IBP.
Plant Filter	-keep default-	Optionally, define filtering for plant data.
Process Unchanged Data	-keep default-	<p>If you want to skip unchanged data, regardless of SAP IBP global parameter setting for this behavior, set this parameter to false.</p> <p>If you want to process unchanged data, regardless of SAP IBP global parameter setting, set this parameter to true.</p> <p>If you leave this parameter field empty, SAP IBP global parameter will determine the behavior.</p>

To use the values defined in the [Define Default Values for Data Integration Between SAP IBP and SAP S/4HANA Cloud](#) integration flow, use the `-keep default-` value for the relevant parameters. This is also the default value of all parameters for which you can maintain a reusable default value in the [Define Default Values for Data Integration Between SAP IBP and SAP S/4HANA Cloud](#) integration flow.

3.4 Working with Field Extensions

With field extensions, you can specify additional attributes to integrate data from and change data mapping.

In general, the required syntax of the value of the `Field Extensions` parameter is the following:

Sample Code

```
<FIELDNAME value = 'DESIRED VALUE' skip="DESIRED VALUE" nil = "DESIRED VALUE" >
```

Note

The `FIELDNAME` must be a field that is listed in the `Attributes in SAP IBP` parameter.

The `DESIRED VALUE` can be defined as a constant value, such as "0" or "TEXT". If you use a constant value, all the rows are filled with this value for the given field. The entered values of `skip` and `nil` are evaluated as either true or false. The value entered after `skip` is skipped, and the value entered after `nil` is nullified. Note that using the `skip` and `nil` parameters is optional, and that instead of skipping a constant value, you can skip mapping itself.

You can also define the `DESIRED VALUE` as a function mixed with an XPath expression. This way, you can select specific values from the data set or define a logic using exact values.

Example

Using the following code, you can define `CUSTOMFIELD` to be `CustomfieldXXX` where `XXX` is the ID of the corresponding row in the data set:

```
<CUSTOMFIELD value = "concat('Customfield', ./ID)" >
```

Example

Using the following code, you can skip the field for a certain ID value:

```
<CUSTOMFIELD value = "./DESIREDFIELD" skip = "ID='ID value'" >
```

You can define an evaluation like the above for any of the fields and with different logical functions. Operations such as `FIELD != ''` also work.

Note

The value of the `DESIREDFIELD` can be any of the fields that are requested from SAP S/4HANA Cloud. In the CDS view, you can check which fields are included in the request. You cannot extend the list of the fields in the request, however, you can cycle through the values of the data set using an XPath expression.

In general, the data structure of an XPath expression looks as follows:

Sample Code

```
<item>
  <field1>value1a</field1>
  <field2>value1b</field2>
</item>
<item>
  <field1>value2a</field1>
  <field2>value2b</field2>
</item>
```

...

Based on the above sample, to select `value1a` and `value2a`, use `./field1`, and to select `value1b` and `value2b`, use `./field2`.

Note that the structure of the data can be different at this stage, therefore, it is recommended to always check the structure of the data set before executing the XPath selection.

Note

Although the integration flow validates the syntax of the field extension XML, you need to make sure that its content is defined according to your business needs.

Extending Plant Data

Example

Sample Code

```
<LOCIDDISPLAY  
value="concat('Plant: ',Plant)" skip="not(Plant=('1020','1000','1010'))"  
nil="Plant='1010'"/>  
<LOCBUPAID  
value="concat('BuPa of plant ',./Plant)"/>  
<LOCREGION value="if(./Plant='1010')then concat('region of ',./Plant)  
else 'other region'"/>
```

The above code makes the following modifications:

- Excludes plants with the IDs 1020, 1000, and 1010 from the integration.
- If the plant ID is 1010, it is replaced with null.
- If the location business partner ID (LOCBUPAID) becomes BuPa of plant <plant ID>.
- The region of the plant with the ID 1010 becomes `region of 1010`, while the region values of all other plants become `other region`.

In this case, the following output is generated based on the parameter value:

```
<LOCID>1000</LOCID>  
<LOCIDDISPLAY>Plant: 1000</LOCIDDISPLAY>  
<LOCBUPAID>BuPa of Plant 1000</LOCBUDPAID>  
<LOCREGION>other region</LOCREGION>  
<LOCID>1010</LOCID>  
<LOCIDDISPLAY></LOCIDDISPLAY>  
<LOCBUPAID>BuPa of Plant 1010</LOCBUDPAID>  
<LOCREGION>region of 1010</LOCREGION>  
<LOCID>1020</LOCID>  
<LOCIDDISPLAY>Plant: 1020</LOCIDDISPLAY>  
<LOCBUPAID>BuPa of Plant 1020</LOCBUDPAID>  
<LOCREGION>other region</LOCREGION>  
<LOCID>1030</LOCID>  
<LOCBUPAID>BuPa of Plant 1030</LOCBUDPAID>  
<LOCREGION>other region</LOCREGION>
```

3.5 Scheduling the Integration Flow

You can schedule the execution of the integration flow under ► *Configure* ► *Timer* ▾.

By default, the start of the integration is scheduled for 2100-01-01 to prevent unnecessary integration jobs during the initial deployment. After you've finalized the configuration of the integration flow, you can manually set the timer according to your needs.

You can select *Run Once* to start integration directly. You can also schedule the job for a future date or make it recurring. For more information about scheduling, see <https://help.sap.com/docs/cloud-integration/sap-cloud-integration/define-timer-start-event>.

4 Troubleshooting

The following examples of errors and their possible solutions might help you troubleshoot your integration process:

- **Integration fails after successful batch creation**

Output Code

```
org.apache.camel.RuntimeCamelException:
com.sap.gateway.core.ip.component.exceptions.OData4Exception: <base
URL>/sap/opu/odata4/sap/cdi_cds/cdi_cds/sap/i_plant/0001/, cause:
java.net.SocketTimeoutException: Read timed out (local port <port number>
to address <IP address> (<GUID>), remote port <port number> to address <IP
address>)
```

To resolve this issue, try again later or check your SAP S/4HANA system for issues.

- **The certificate in use has expired**

Output Code

```
org.apache.camel.RuntimeCamelException:
com.sap.gateway.core.ip.component.exceptions.OData4Exception: Received
fatal alert: certificate_expired, cause:
javax.net.ssl.SSLHandshakeException: Received fatal alert:
certificate_expired
```

To resolve this issue, renew the certificate.

- **Fields are missing from the Attributes in SAP IBP parameter, which are included in the Field Extensions parameter**

Output Code

```
javax.script.ScriptException: java.lang.Exception: java.lang.Exception:
Fields are missing from the Attributes in SAP IBP parameter which
are included in the Field Extensions parameter. Missing fields:
[GEOLONGITUDE]@ line 56 in Validations.groovy, cause: java.lang.Exception:
Fields are missing from the Attributes in SAP IBP parameter which are
included in the Field Extensions parameter. Missing fields: [GEOLONGITUDE]
```



To resolve the issue, align the value of the Attributes in SAP IBP parameter with the mapping defined in the Field Extensions parameter.

Important Disclaimers and Legal Information

Hyperlinks

Some links are classified by an icon and/or a mouseover text. These links provide additional information.

About the icons:

- Links with the icon : You are entering a Web site that is not hosted by SAP. By using such links, you agree (unless expressly stated otherwise in your agreements with SAP) to this:
 - The content of the linked-to site is not SAP documentation. You may not infer any product claims against SAP based on this information.
 - SAP does not agree or disagree with the content on the linked-to site, nor does SAP warrant the availability and correctness. SAP shall not be liable for any damages caused by the use of such content unless damages have been caused by SAP's gross negligence or willful misconduct.
- Links with the icon : You are leaving the documentation for that particular SAP product or service and are entering an SAP-hosted Web site. By using such links, you agree that (unless expressly stated otherwise in your agreements with SAP) you may not infer any product claims against SAP based on this information.

Videos Hosted on External Platforms

Some videos may point to third-party video hosting platforms. SAP cannot guarantee the future availability of videos stored on these platforms. Furthermore, any advertisements or other content hosted on these platforms (for example, suggested videos or by navigating to other videos hosted on the same site), are not within the control or responsibility of SAP.

Beta and Other Experimental Features

Experimental features are not part of the officially delivered scope that SAP guarantees for future releases. This means that experimental features may be changed by SAP at any time for any reason without notice. Experimental features are not for productive use. You may not demonstrate, test, examine, evaluate or otherwise use the experimental features in a live operating environment or with data that has not been sufficiently backed up.

The purpose of experimental features is to get feedback early on, allowing customers and partners to influence the future product accordingly. By providing your feedback (e.g. in the SAP Community), you accept that intellectual property rights of the contributions or derivative works shall remain the exclusive property of SAP.

Example Code

Any software coding and/or code snippets are examples. They are not for productive use. The example code is only intended to better explain and visualize the syntax and phrasing rules. SAP does not warrant the correctness and completeness of the example code. SAP shall not be liable for errors or damages caused by the use of example code unless damages have been caused by SAP's gross negligence or willful misconduct.

Bias-Free Language

SAP supports a culture of diversity and inclusion. Whenever possible, we use unbiased language in our documentation to refer to people of all cultures, ethnicities, genders, and abilities.

© 2024 SAP SE or an SAP affiliate company. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP SE or an SAP affiliate company. The information contained herein may be changed without prior notice.

Some software products marketed by SAP SE and its distributors contain proprietary software components of other software vendors. National product specifications may vary.

These materials are provided by SAP SE or an SAP affiliate company for informational purposes only, without representation or warranty of any kind, and SAP or its affiliated companies shall not be liable for errors or omissions with respect to the materials. The only warranties for SAP or SAP affiliate company products and services are those that are set forth in the express warranty statements accompanying such products and services, if any. Nothing herein should be construed as constituting an additional warranty.

SAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP SE (or an SAP affiliate company) in Germany and other countries. All other product and service names mentioned are the trademarks of their respective companies.

Please see <https://www.sap.com/about/legal/trademark.html> for additional trademark information and notices.