



Integration Guide | PUBLIC

Document Version: 1.1 – 2024-05-15

Integrating Planned Independent Requirement Data from SAP Integrated Business Planning to SAP S/4HANA Cloud

Integrating SAP IBP for Supply Chain 2402 with SAP S/4HANA Cloud Using SAP Cloud Integration

Content

- 1 Introduction. 4**
- 2 Prerequisites. 5**
- 3 How to Use the Integration Flow? 6**
 - 3.1 Configuring the Integration Flow. 6
 - Configuring the Authentication. 7
 - Data Mapping. 7
 - Defining Additional Parameters. 8
 - Adding Further Filters to the Integration Flow. 10
 - Scheduling the Integration Flow. 11
- 4 Troubleshooting. 12**

Document History

The following table provides an overview of the most important changes.

Version	Date	Description
1.1	May 15, 2024	Parameters have been updated in Defining Additional Parameters [page 8] section.
1.0	February 16, 2024	Initial version

1 Introduction

Using the integration flow, you can integrate data from SAP S/4HANA Cloud, as part of the solution SAP S/4HANA Cloud Public Edition to SAP Integrated Business Planning for Supply Chain (SAP IBP). Using this data, you can perform demand forecasting in SAP IBP, then integrate the results back to SAP S/4HANA Cloud as planned independent requirements.

Data integration between SAP IBP and SAP S/4HANA Cloud using the integration flows in the *SAP IBP - Integration with SAP S/4HANA Cloud* package is available with SAP IBP 2402 and higher.

The *Integrate KFs from SAP IBP to SAP S/4HANA Cloud as Planned Independent Requirements* integration flow collects the results of demand forecasting in SAP IBP as planned independent requirements and transfers them to your SAP S/4HANA Cloud system via a dedicated OData API.

The collected data is stored in your planning area based on the `SAPIBP1` or the `SAP6` sample planning area in the consensus demand plan quantity (`FINALDEMANDPLANNINGQTY`) key figure. Data is stored at technical week product location customer level. The key figure data is collected for every location and product combination on the selected time aggregation level and transformed to the appropriate OData format for the `Planned Independent Requirements` OData API. For more information about the API, see the API reference at the SAP Business Accelerator Hub at https://api.sap.com/api/API_PLND_INDEP_RQMT_SRV.

2 Prerequisites

We recommend that you have configured frequently used parameters using the *Define Default Values for Data Integration Between SAP IBP and SAP S/4HANA Cloud* integration flow.

3 How to Use the Integration Flow?

After copying the integration flow, configure it according to your needs.

Time Aggregation

When the value of the `FINALDEMANDPLANNINGQTY` key figure is retrieved from SAP Integrated Business Planning for Supply Chain (SAP IBP), you can set the `Period Type - Time Profile Level` externalized parameter to any period level. However, if it's set to 1, which corresponds to the daily time profile level in the `SAPIBP1` sample planning area, no key figure data is integrated from SAP IBP, as the `WKPRODLCCUST` planning level is defined at technical week level, and disaggregation during key figure retrieval is not supported in this case.

Another crucial externalized parameter is `Period Type`, which defines the period type during the upload phase of the integration. If it's set to **week**, data is uploaded at calendar week time level. If the `Period Type - Time Profile Level` parameter is also set to calendar week (**3**), everything works as expected. However, if it's set to **Month**, the values of four calendar weeks within the same month are uploaded, resulting in a duplicate period error in the OData service. Therefore, it's essential to align the configuration of these two external parameters for a successful data extraction.

For more information about the configuration of externalized parameters, see [Defining Additional Parameters \[page 8\]](#).

Setting the Unified Base Unit

Setting the unified base unit allows you to query planned independent requirement data from SAP IBP with their base unit of measure without having to set the base unit of measure for each product in the query. By default, `1BU` is used as the unified base unit.

📘 Note

We recommend that you do not change the default base unit of measure unless `1BU` is not available in your SAP IBP system.

3.1 Configuring the Integration Flow

3.1.1 Configuring the Authentication

The integration flow connects to both the SAP S/4HANA Cloud and the SAP IBP system. Connections, including the authentication method, must be created and configured at different places depending on the respective system. Once the connections are created for both directions, you need to configure them in the integration flow under ► [Configure](#) ► [Receiver](#) ►.

Authentication Methods for the Connection to SAP IBP

You can only choose basic authentication when connecting to SAP IBP. You can configure the authentication method during the configuration of the destination. You can set the name of the destination using the `Destination for SAP IBP` parameter of the integration flow.

For more information, see [Setting Up the Integration](#).

Authentication Methods for the Connection to SAP S/4HANA Cloud

The following authentication methods are available when connecting to SAP S/4HANA Cloud:

- Basic authentication
- Client certificate (X.509 certificate)

You can select the authentication method in the integration flow under ► [Configure](#) ► [Receiver](#) ► [Authentication](#) ►. Although there are more options displayed in the list, only basic authentication and client certificate authentication are supported.

The default authentication method is client certificate.

Setting Up the Client Certificate Authentication Method

As a prerequisite of using a client certificate, add and deploy the required key pair to the keystore. You can do so in SAP Integration Suite using the [Keystore](#) tile in the [Manage Security](#) section under [Monitoring Artifacts](#). For more information, see <https://help.sap.com/docs/cloud-integration/sap-cloud-integration/managing-keystore-entries>.

If you select authentication using a client certificate when configuring the integration flow, you need to enter the private key alias.

Setting Up the Basic Authentication Method

As a prerequisite of using basic authentication, create and deploy the user credentials type of security material. You can do so in SAP Integration Suite using the [Security Material](#) tile in the [Manage Security](#) section under [Monitoring Artifacts](#). For more information, see <https://help.sap.com/docs/cloud-integration/sap-cloud-integration/managing-security-material>.

If you select basic authentication when configuring the integration flow, you need to enter the credential name.

3.1.2 Data Mapping

You can map the fields of the `Planned Independent Requirements` OData API to attributes in SAP Integrated Business Planning for Supply Chain (SAP IBP) for data integration.

The following default data mapping is available in the integration flow:

Field in OData API	Field in SAP IBP	Further Hints
Product	PRDID	The field in SAP IBP is the attribute defined in the <code>Product Source Field</code> parameter.
Plant	LOCID	The field in SAP IBP is the attribute defined in the <code>Plant Source Field</code> parameter.
MRPArea	LOCID	The field in SAP IBP is the attribute defined in the <code>Plant Source Field</code> parameter.
PlndIndepRqmtVersion		This value can't be edited. It is set to 00.
PlndIndepRqmtPeriod	TSTFR	The field in SAP IBP is the starting time stamp of the period that belongs to the key figure.
PeriodType		The field in SAP IBP is the attribute defined in the <code>Period Type</code> parameter. The default value is set to week.
PlannedQuantity	FINALDEMANDPLANNINGQTY	The field in SAP IBP is the attribute defined in the <code>Key Figure Name</code> parameter.

3.1.3 Defining Additional Parameters

Under [Configure > More](#), you can find the following parameters that you can use to configure the integration flow:

Parameter Name	Default Value	How to Configure the Parameter?
Batch Size in Rows	50000	Define the size of the OData batch during data reading.
Destination for SAP IBP	-keep default-	Enter the name of the SAP IBP system from which planned independent requirements are collected.
Filter ID		Optionally, enter the ID of a planning filter to narrow down data collection.

Parameter Name	Default Value	How to Configure the Parameter?
Filter User ID		To use a predefined filter, also define a user.
Further Filters		Optionally, define additional filters for planned independent requirements. For more information, see Adding Further Filters to the Integration Flow [page 10] .
Host for SAP S/4HANA Cloud	-keep default-	Define the base URL of the SAP S/4HANA Cloud API
Key Figure Name	FINALDEMANDPLANNINGQTY	Enter the name of the key figure in which the result of the monthly consensus demand quantities are stored after demand planning in SAP IBP.
Package Size in Rows	100000	Optionally, define the package size of reading data from SAP IBP.
Parallel Processes	5	Optionally, define the number of OData calls to be run in parallel during data integration to SAP S/4HANA Cloud.
Period Type	week	Define the period type in SAP S/4HANA Cloud. You can use one of the following options: <ul style="list-style-type: none"> • week • month • day
Period Type - Time Profile Level	3	Define the time profile level in SAP IBP to be used as aggregation level for data collection.
Planning Area	-keep default-	Define the planning area in SAP Integrated Business Planning for Supply Chain from which you want data to be collected.
Planning Area Version	-keep default-	Define the version of the source planning area in SAP IBP.
Plant Source Field	LOCID	Define the attribute in SAP IBP to which the plant key attribute is integrated from SAP S/4HANA Cloud.

Parameter Name	Default Value	How to Configure the Parameter?
Product Source Field	PRDID	Define the attribute in SAP IBP to which the product key attribute is integrated from SAP S/4HANA Cloud.
Read Limit		Optionally, define the maximum number of rows to be collected from SAP IBP.
Unified Base Unit	-keep default-	Define the base unit of measure.

To use the values defined in the [Define Default Values for Data Integration Between SAP IBP and SAP S/4HANA Cloud](#) integration flow, use the `-keep default-` value for the relevant parameters. This is also the default value of all parameters for which you can maintain a reusable default value in the [Define Default Values for Data Integration Between SAP IBP and SAP S/4HANA Cloud](#) integration flow.

3.1.4 Adding Further Filters to the Integration Flow

To filter data integrated from SAP IBP, you can use the `Further Filters` parameter in the integration flow configuration.

In the filter expression, you can use the following OData operators and functions:

- Relational operators
These operators are `EQ`, `NE`, `LT`, `LE`, `GT`, `GE`, and `LIKE`.
- Logical operators
These operators are `AND`, `NOT`, `OR`, `(, and)`.
- Functions
These functions are `STARTSWITH`, `ENDSWITH`, and `SUBSTRINGOF`.

You can also apply further filters on period levels. To do so, use the following pattern:

Sample Code

```
PERIOD_LEVEL_* and PERIOD_LEVEL_*_REL
```

Example

The following example selects planned independent requirement data related to the `EXAMPLEPRODUCTID` product and has a higher value than 100:

Sample Code

```
FINALDEMANDPLANNINGQTY gt 100 AND PRDID eq 'EXAMPLEPRODUCTID'
```

❖ Example

The following example selects planned independent requirement data for the next week or later:

🔗 Sample Code

```
PERIOD_LEVEL_2_REL ge 1
```

3.1.5 Scheduling the Integration Flow

You can schedule the execution of the integration flow under **Configure > Timer**.

By default, the start of the integration is scheduled for 2100-01-01 to prevent unnecessary integration jobs during the initial deployment. After you've finalized the configuration of the integration flow, you can manually set the timer according to your needs.

You can select *Run Once* to start integration directly. You can also schedule the job for a future date or make it recurring. For more information about scheduling, see <https://help.sap.com/docs/cloud-integration/sap-cloud-integration/define-timer-start-event>.

4 Troubleshooting

In case an error occurs during integration, you can check the following attachments in the *Monitor Message Processing* view:



- *Failed Planned Independent Requirements*
In the *Failed Planned Independent Requirements* attachment, you can find all planned independent requirement items and their rejection messages.
- *Parameters*
In the *Parameters* attachment, you can find all the parameters of the *Integrate KFs from SAP IBP to SAP S4HANA Cloud as Planned Independent Requirements* integration flow together with the parameters of the *Define Default Values for Data Integration Between SAP IBP and SAP S4HANA Cloud* integration flow. In this attachment, you can check the values of the parameters that were used when creating the query and scheduling the upload after the query.
- *Error Messages*
The *Error Messages* attachment contains all types of error messages coming from SAP IBP. This attachment is only available if errors occurred.

Important Disclaimers and Legal Information

Hyperlinks

Some links are classified by an icon and/or a mouseover text. These links provide additional information.

About the icons:

- Links with the icon : You are entering a Web site that is not hosted by SAP. By using such links, you agree (unless expressly stated otherwise in your agreements with SAP) to this:
 - The content of the linked-to site is not SAP documentation. You may not infer any product claims against SAP based on this information.
 - SAP does not agree or disagree with the content on the linked-to site, nor does SAP warrant the availability and correctness. SAP shall not be liable for any damages caused by the use of such content unless damages have been caused by SAP's gross negligence or willful misconduct.
- Links with the icon : You are leaving the documentation for that particular SAP product or service and are entering an SAP-hosted Web site. By using such links, you agree that (unless expressly stated otherwise in your agreements with SAP) you may not infer any product claims against SAP based on this information.

Videos Hosted on External Platforms

Some videos may point to third-party video hosting platforms. SAP cannot guarantee the future availability of videos stored on these platforms. Furthermore, any advertisements or other content hosted on these platforms (for example, suggested videos or by navigating to other videos hosted on the same site), are not within the control or responsibility of SAP.

Beta and Other Experimental Features

Experimental features are not part of the officially delivered scope that SAP guarantees for future releases. This means that experimental features may be changed by SAP at any time for any reason without notice. Experimental features are not for productive use. You may not demonstrate, test, examine, evaluate or otherwise use the experimental features in a live operating environment or with data that has not been sufficiently backed up.

The purpose of experimental features is to get feedback early on, allowing customers and partners to influence the future product accordingly. By providing your feedback (e.g. in the SAP Community), you accept that intellectual property rights of the contributions or derivative works shall remain the exclusive property of SAP.

Example Code

Any software coding and/or code snippets are examples. They are not for productive use. The example code is only intended to better explain and visualize the syntax and phrasing rules. SAP does not warrant the correctness and completeness of the example code. SAP shall not be liable for errors or damages caused by the use of example code unless damages have been caused by SAP's gross negligence or willful misconduct.

Bias-Free Language

SAP supports a culture of diversity and inclusion. Whenever possible, we use unbiased language in our documentation to refer to people of all cultures, ethnicities, genders, and abilities.

© 2024 SAP SE or an SAP affiliate company. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of SAP SE or an SAP affiliate company. The information contained herein may be changed without prior notice.

Some software products marketed by SAP SE and its distributors contain proprietary software components of other software vendors. National product specifications may vary.

These materials are provided by SAP SE or an SAP affiliate company for informational purposes only, without representation or warranty of any kind, and SAP or its affiliated companies shall not be liable for errors or omissions with respect to the materials. The only warranties for SAP or SAP affiliate company products and services are those that are set forth in the express warranty statements accompanying such products and services, if any. Nothing herein should be construed as constituting an additional warranty.

SAP and other SAP products and services mentioned herein as well as their respective logos are trademarks or registered trademarks of SAP SE (or an SAP affiliate company) in Germany and other countries. All other product and service names mentioned are the trademarks of their respective companies.

Please see <https://www.sap.com/about/legal/trademark.html> for additional trademark information and notices.